Last Updated 1/14/2016

This survey follows 'The National Marsh Bird Monitoring (NMBM) Program Protocols'. Details about this program, current methodologies and data management are available on the Programs website: http://www.cals.arizona.edu/research/azfwru/NationalMarshBird/, in the 'Field Methods' portion of the website. Using site-specific protocol, we target three species: American Bittern (Botaurus lentiginosus), the Sora (Porzana carolina), and the Virginia Rail (Rallus limicola).

What to Take in the Field:	
	Blank datasheets
	Trimble with established survey sites
	Pencils
	Clip board
	Binoculars
	Speakers
	MP3 player with correct calls loaded in the correct order
	Digital sound meter reader
	Compass
	YSI meter
	Range finder
	Waders
	Marsh boat
	Ziplock bags to put the equipment in to keep it dry

Survey Prep:

- 1. Located the MP3 player, sound meter and speakers and ensure:
 - a. Enough batteries are available to get through the survey season, if not, order more batteries
 - b. Place fresh batteries are in the equipment*
 - c. Make sure you are comfortable using the equipment
 - d. You know how to work the sound meter to meet the criteria outlined in the Official NMBM methodology.
 - *Be sure to never store batteries in the equipment. Take the batteries out and place them in the same storage bag as the equipment to prevent the batteries from corroding inside the battery compartments.
- 2. Download current datasheets from the **NMBM** → **Field Methods** website listed above.
- 3. Do a preliminary site visit and practice protocols.
- 4. Make sure you are familiar with all calls from the three target species.
- 5. Read the YSI meter methodologies located in the **1.04 and 1.06 Spring and Management Unit Water Monitoring Quality Protocol** ISI to make sure you are familiar with the equipment.
- 6. Prior to monitoring, **permanent survey sites will need to be established for Avocet unit** (which was dry during the pilot study). You can contact Jo Ann Dullum, or an IMP GIS Manager for assistance.
 - a. Wetland habitat boundaries (from the NVC shapefile) can be used to 'bound' the creation of randomly generated points that can be used for Avocet.

Last Updated 1/14/2016

- b. Survey sites need to be selected from randomly generated points. Start with the first point (It will have the **lowest 'FID' value** in **the attribute table**), if that point meets survey criteria (i.e. isn't in an upland area instead of a wetland), use it. If not, move to the next site. If it doesn't meet survey criteria, eliminate this site and move to the next on the list. Continue this process until 5-8 sites that meet the survey criteria have been located. (This is why step 3 will be very important!)
- c. Merge these new sites with the existing **'2014_EstSurveySites'** shapefile to create a new shapefile will all of the permanently established survey sites.
- 7. Map sure the 'Secretive Marsh Bird Map' is loaded on the Trimble/s you will be using. (See the *Locating Survey Sites* portion of the ISI).

Conducting Surveys:

- 1. There are three survey routes establish, but a fourth will need to be developed for Avocet Unit .
- 2. Each <u>survey site will need to be visited three times</u> over three months (once per month).
- 3. Follow the survey protocol guidelines within the NMBM protocol when conducting the surveys.
- 4. Make sure to get the current weather data before you head out to conduct the surveys.
- 5. In keeping with NMBM protocol, only conduct surveys on days with little to no wind and no rain.
- 6. Be sure to fill in **all** data fields for each site visited.
- 7. **Do not** forget to collect the water quality data when you conduct the surveys.
- 8. <u>Visit all sites on a route</u> on the same morning.

Data Entry:

- 1. Data should be recorded in the NMBM database.
- 2. You will need to contact **Jo Ann Dullum** to get set up with access to enter the data.
- 3. You can also record the data into a shapefile (see the '2014_Recorded_Presence' shapefile* located at I:\GIS DATA and MAPS\Shape_files\birds\Secretive marsh bird project\ for an example)
 - *Please note that the locations within this shapefile were created using the survey point's established GPS coordinates and the recorded distance and bearing for each recorded individual.
- 4. A datasheets should be saved and placed in a secretive marsh bird folder.

Last Updated 1/14/2016

Locating Survey Sites:

PRIOR TO HEADING INTO THE FIELD:

1) Turn on the Trimble.

a) Turn on the unit to be used by tapping the green power button toward the bottom of the Trimble unit. Depending on the unit series (2000 or 6000), the boot up process may take a few minutes.

2) Check the Battery Level.

- a) Check the battery level by looking at the battery icon in the upper right corner of the screen.
 - i) Make sure the battery has 3-4 vertical bars showing.
 - (1) If there are less than 3 bars and you are planning on using the Trimble for a long period that day, consider switching to another Trimble unit with more battery life if available and <u>make sure to turn off the current unit</u>* (see below for proper instructions to ensure the unit is turned off and not sleeping) and place the unit on its correct charging port.
 - (2) If you see a red '!' within the battery icon, this Trimble has very low battery life and is not going to be usable in the field at this time and you will need to switch to another Trimble unit. When this happens, make sure to turn off the current unit* and place the current unit on its correct charging port, this unit will not be useable in the field for several hours.
 - *If the unit is not turned off properly prior to charging, the unit may not charge properly causing a further delay prior to it being usable in the field.

3) Open ArcPad and see if the 'Secretive Marsh Bird' Map is loaded on that Trimble.

- a) Open ArcPad.
 - i) For the **2000** series: Use the attached stylus to tap on the 'Start' button located in the <u>upper</u> left corner of the screen a drop down menu should appear. From the menu, tap on the 'ArcPad' icon to open the program. Wait for the program to open completely.
 - ii) For the **6000** series: Use the stylus to tap on the 'Windows' icon located in the lower left corner of the startup screen this should send you to anther screen with several program icons available. Use your stylus to scroll down the screen by dragging the tip from the lower portion of the screen to the upper portion. Continue to scroll down until you see the 'ArcPad' icon appear. Tap on the 'ArcPad' icon to open the program. Wait for the program to open completely.

b) Check to see if 'Secretive Marsh Bird' 'Map is loaded on that Trimble.

- i) Once ArcPad opens, tap the 'Choose Map to Open' option.
- ii) Looks under the 'Folder' column for the 'Water Spring Flow Sites' Map.
 - iii) If it is there select that map and go to step 5. If it is not there, go to step 4.

4) Add 'Secretive Marsh Bird" Map to Trimble Unit.

- a) Open the 'Secretive Marsh Bird' Map in GIS.
 - i) On a computer with GIS, open ArcMap.
 - ii) Once ArcMap opens a box will appear with options. On the left-hand side of the box, under 'Existing Maps' select 'Browse for more...'
 - iii) Navigate to: I:\GIS DATA and MAPS\Maps\ Animal_maps\birds
 - iv) Select 'Secretive Marsh Bird'.

Last Updated 1/14/2016

- b) Export ArcMap 'Secretive Marsh Bird' Map to an ArcPad 'Secretive Marsh Bird' formatted Map.
 - i) Make sure the ArcPad Data Manager toolbar is accessible. If it appears on the main screen, go to **step 4-b-ii**.
 - ii) Add the toolbar to the main screen by going to 'Customize' → 'Toolbars' → and click on 'ArcPad Data Manager'.

*If the icons on the 'ArcPad Data Manager' are greyed out, you will need to active the toolbar by going to 'Customize' > 'Extensions'-> and checking the box by 'ArcPad Data Manager'.

- iii) Click on the icon that looks like a Trimble with an arrow pointing to the right.
- iv) You are not checking out an RLGIS shapefile database for this, click 'No'.
- v) In the window that appears, the middle column is titled 'Actions'; click in that column next to where it says 'Secretive Marsh Bird' (you can click and drag a column divider to expand a column to see the entire name) and select 'Export as background data'

 'Make read only'.
- vi) Repeat step 4-b-v for 'Management Units' and click 'Next'.
- vii) Do not do anything in this screen except click 'Next'.
- viii) In the middle **right** of the pop-up box, there is an icon that looks like a **folder**. Click on this icon and navigate to: **!:\GIS DATA and MAPS\All Trimble Check In** and **save the map**. <u>Make sure you remember where you save this map</u>; you will need it in future steps.
- ix) In this window, in the lower **right** section, there is a **white box** with '*Map Name*' to its left. In this box **name the map**; chose something short but clear. Click '*Next*'.
- x) On the new screen, click 'Finish'.
- xi) A **report** will appear letting you know if everything transferred properly. Click **'Ok'**.
- xii) You can now close out of ArcMap if you want.

c) Connect Trimble to Computer.

- i) If you still have ArcPad open on your Trimble, close the program by tapping on the upper left icon (Trimble in a circle) and selecting 'exit'.
- ii) Make sure the proper connecting cable is plugged into the computer. For the **2000 series** it will be a charging cradle, for the **6000 series** it will be a USB cord.
- iii) On your computer, go to 'Start' → 'All Programs' → 'Windows Mobile Device Center'. If a white pop-up window appears asking about setting up the Trimble, exit out of the window.
- iv) Once 'Windows Mobile Device Center' is opened, with your Trimble still turned on, attached it to its charger or USB cable (see step 4-b-ii). On the Trimble screen a pop-up box will appear letting you know it is connecting. It will also say 'Connecting' on the 'Windows Mobile Device Center' screen in the lower left corner. Once it is connected, the pop-up box on the Trimble will disappear and the 'Windows Mobile Device Center' screen will say 'Connected'* in the lower left corner. If a white pop-up window appears asking about setting up the Trimble, exit out of the window.

*If it does not connect, repeat the step a couple more times. If it still doesn't want to work, you may need to re-start your computer. That will usually allow it to connect.

v) Repeat steps 4-c-i thru 4-c-iv.

Last Updated 1/14/2016

- d) Move ArcPad 'Secretive Marsh Bird' formatted Map onto Trimble device.
 - i) Once connected, select 'Connect without setting up your device'.
 - ii) Select 'File Management' → 'Browse the contents of your device'.
 - iii) In the pop-up box that opens, double click the disk icon in the box on the right and navigate to 'My Documents'. Leave that window open.
 - iv) On your computer, click 'Start' -> 'Computer' to open a 'new file window'.
 - v) In that 'new file window', navigate to where you just saved the ArcPad 'Secretive Marsh Bird' formatted Map from step 4b and copy the entire file.
 - vi) Paste the Map you just copied in the 'new file window' into the 'My Documents' file in the 'Windows Mobile Device Center' screen. A pop-up window will appear with a 'status bar' indicating the progress of the transfer. Once that box closes the transfer is complete.
 - vii) The map should now be loaded onto the Trimble. Close the 'Windows Mobile Device Center' window and remove the Trimble from the cradle or cable.
 - viii) Go back to step 3.

5) Turn on the GPS function and make sure satellites acquire properly.

- a) Turn on the GPS Function.
 - i) Do this outside* <u>prior</u> to heading into the field. That way if there are any problems are right by the office for assistance and/or to switch out Trimble units if necessary.
 - *Turning this feature on before heading outside will cause the battery to drain quickly as it tried to search for satellites from within the building.
 - ii) In the top toolbar, tap on the icon. A second toolbar will appear underneath the top toolbar.
 - iii) On the second toolbar, tap on the hicon. It should (temporarily) turn blue and a red box should appear at the bottom of the screen with the words 'No Fix'.

 If this does not happen, tap on the black down arrow located immediately below the hicon. A dropdown menu should appear.
 - iv) Within the drop down menu, look for the heading 'GPS Active' with * icon to its left. If there is not a red box outline around the icon, tap once on the 'GPS Active' heading. The dropdown menu should disappear and a red box should appear at the bottom of the screen with the words 'No Fix'. If there is a red box outline around the icon, the the GPS function has already been turned on.

b) Acquiring Satellites and Current Position.

- i) Once the GPS function has been turned on, it will immediately start trying to acquire satellite signal. You must be outside and should not be too near buildings for this to work successfully.
- ii) While it is trying to acquire the satellites, the **red** box with the words 'No Fix' will continue to stay red. Additionally, you will get a white pop-up window that appears periodically with the message "No current position fix at this time."
- iii) Once the GPS has a strong enough signal, the **red** box with the words 'No Fix' will turn **green** and the pop-up box will stop appearing. You can tap the small 'x' in the upper right corner of the **green** box to make it disappear so that you can better see the underlying map.

Last Updated 1/14/2016

- iv) You may lose signal on occasion in the field, especially when in a car. When this happens the popup box will reappear and keep appearing until you get a strong enough signal.
- v) **Be careful when using the Trimble in a vehicle**. The vehicle may be moving faster than the Trimble is re-acquiring your current position. This can cause a 'lag' effect that can cause you to overshoot your destination.

USING THE TRIMBLE IN THE FIELD:

- 1) Viewing the full extent of the map loaded on the Trimble.
 - a) Zoom out to see the full map that has been loaded.
 - i) In the top toolbar, tap on the or icon. A second toolbar will appear.
 - ii) Tap on the **black** arrow directly under the icon second from the left.
 - iii) Select the 'Zoom to Full Extent' option.
 - iv) The icon above the black arrow will now change to .
 - v) Tap the icon once to view the full extent of the map loaded to the Trimble.
- 2) How to adjust your view of the underlying map to a certain area.
 - a) Zooming in/out to a specific area. *
 - i) In the top toolbar, tap on the or icon. A second toolbar will appear
 - ii) Tap on the **black** arrow directly under the left most icon.
 - iii) Tap on the option that you want, either 'Zoom In' or 'Zoom Out'.
 - iv) The icon above the black arrow will now change to either [♠] or [♠]**.
 - v) Use your stylus to draw a square around the area you want to zoom to. Do this by placing the tip of the stylus to the top left of the area and then (while keeping continuous contact) dragging the stylus in a downward diagonal to your right.
 - vi) The size of the box will impact the magnitude of the zoom. A small box will zoom the image further in or out than a larger box. *
 - *Keep in mind that once the GPS function is turned on and has acquired satellites, current Trimble settings will not allow you to zoom into an area that does not include your current position.
 - **If the icon you need is already the one that appears above the black arrow, then all you need to do is tap the icon prior to using your stylus on the screen.
 - b) How to 'Pan' (move the screen without zooming)
 - i) In the top toolbar, tap on the oicon. A second toolbar will appear
 - ii) Tap on the **black** arrow directly under the left most icon.
 - iii) Tap on the 'Pan' option.
 - iv) The icon above the black arrow will now change to
 - v) Tap the screen to 'grab' it and without lifting the stylus, drag the image to the desired location.

Last Updated 1/14/2016

c) Going back to your previous zoom extent.

- i) This function can be used if you unintentionally zoom too far in or out, or if you accidentally move the underlying image so that it is no longer where you need it to be.
- ii) In the top toolbar, tap on the 🍧 icon. A second toolbar will appear underneath the top toolbar.
- iii) Tap on the **black** arrow directly under the third icon from the left.
- iv) Select the 'Go Back to Previous Extent' option.
- v) The icon above the black arrow should now look like 🗘.
- vi) Tap that icon once to go back one 'move'. You can tap the icon more than once if needed.

3) Navigating to a location.

- a) Knowing which way is north.
 - i) The map in the Trimble is loaded so that when looking at the map, 'North' is always at the top of the Trimble (furthest from the 'power' button'). The underlying map does not reorient itself when you move around. In other words, if you have the top of the Trimble pointed east, north on the map will still be at the top of the Trimble. If confused, reorient the Trimble so the the top of the Trimble is pointed north (towards Harrison and Gadwall unit).


4) Knowing where you are on the map.

- a) Understanding the red circle.
 - i) Once the Trimble has acquired a GPS signal, a red circle will appear on the map. This circle indicates where you are in relation to the map.
 - ii) The Trimble settings are currently set so that you cannot zoom into an area of the map that does not include your **red** circle.
 - iii) As you move around in the field, the Trimble unit will automatically adjust the underlying map so that your red circle, and subsequently, the current area you where are located is always in view.
 - iv) Be aware that your 'level of zoom' can impact how close you look to a designated spot. If you are zoomed way out, you may look like you are at a target location when in fact you may be several meters away. If you are zoomed in too close, every slight move will cause your red circle to 'jump' a distance on the screen. Subsequently, as you appear to get closer to a target, you may have to slowly zoom in more and more until you find that 'sweet spot' that lets you know you are where you should be without causing the red circle to jump all over the screen.

5) Closing out of ArcPad at the end of the Day*

*This must be done in order to ensure the data collected during the day is properly saved.

a) Close out of ArcPad



i) Tap the <u>icon in the upper left corner.</u>

- ii) Tap 'Exit'.
- iii) If it asks if you want to save changes, select 'Yes'.
- iv) You may see several processing bars flash across the screen that is okay.
- v) ArcPad is now closed down.